

DG MD TNC 385 FM (943 319)

- Prewired complete unit consisting of a base part with double screw connection and plug-in protection modules; with remote signalling contact connection
- High discharge capacity due to heavy-duty zinc oxide varistors / spark gaps
- High device reliability due to „“Thermo Dynamic Control““ arrester monitoring





Basic circuit diagram



Dimension drawing

Modular surge arrester for use in TN-C systems; with floating changeover contact.

NEW

Type	DG MD TNC 385 FM
Part No.	**943 319**
Technical data	
SPD according to EN 61643-11 / IEC 61643-11	Type 2 + Type 3 / class II + class III
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_C)	385 V (50 / 60 Hz)
Nominal discharge current (8/20 µs) (I_n)	20 kA
Max. discharge current (8/20 µs) (I_{max})	40 kA
Combination wave (U_{OC})	20 kV
Nominal load current for “V-connection” (I_L)	63 A
Voltage protection level (U_P)	≤ 1.75 kV
Voltage protection level at 5 kA (U_P)	≤ 1.35 kV
Response time (t_A)	≤ 25 ns
Max. mains-side overcurrent protection	125 A gG
Max. mains-side overcurrent protection with “V-connection”	63 A gG
Max. mains-side overcurrent protection with stub wiring	125 A gG
Short-circuit withstand capability for max. mains-side overcurrent protection (I_{SCCR})	25 kA_{rms}
Temporary overvoltage (U_T) – characteristic	335 V / 5 sec. – Festigkeit 440 V / 120 min. – Festigkeit
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm^2 solid / flexible
Cross-sectional area (max.) with stub wiring	35 mm^2 stranded / 25 mm^2 fine-stranded
Cross-sectional area (max.) with “V-connection”	16 mm^2 Stranded / fine-stranded
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	3 Standard DIN module, DIN 43880
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm^2 solid / flexible

© DEHN SE • Hans-Dehn-Str. 1 • 92318 Neumarkt • Germany • Tel. +49 9181 906-0 • info@dehn.de • www.dehn.de

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

Masterdata	
Net weight	320 g/pc(s)
GTIN	4013364553910
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363030

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN SE • Hans-Dehn-Str. 1 • 92318 Neumarkt • Germany • Tel. +49 9181 906-0 • info@dehn.de • www.dehn.de

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component