
# DEHNguard modular with Advanced Circuit Interruption (Safe Dimensioning)


## DG M TN ACI 275 FM (952220)

- ACI switch / spark gap combination integrated in the protection module
- Prewired complete unit consisting of a base part and plug-in protection modules
- High reliability due to „“Thermo Dynamic Control““ SPD monitoring device and ACI technology
- No backup protection device required due to ACI technology
- Smaller connection cross-section of 6 mm² always sufficient






Basic circuit diagram




Dimension drawing

Modular surge arrester with Advanced Circuit Interruption (ACI) for single-phase 230 V TN systems.

| **Type** | **DG M TN ACI 275 FM** |
|---|---|
| **Part No.** | **952220** |
| SPD according to EN 61643-11 / IEC 61643-11 | type 2 / class II |
| Energy coordination with terminal equipment (≤ 10 m) | type 2 + type 3 |
| Nominal voltage (a.c.) ($U_N$) | 230 V (50 / 60 Hz) |
| Max. continuous operating voltage (a.c.) [L-PE] ($U_C$) | 275 V (50 / 60 Hz) |
| Max. continuous operating voltage (a.c.) [N-PE] ($U_C$) | 255 V (50 / 60 Hz) |
| Nominal discharge current (8/20 µs) ($I_n$) | 20 kA |
| Voltage protection level [L-PE]/[N-PE] ($U_p$) | ≤ 1.5 / ≤ 1.5 kV |
| Response time ($t_A$) | ≤ 100 ns |
| Additional external fuse necessary | not required |
| Short-circuit withstand capability ($I_{SCCR}$) | 25 $kA_{rms}$ |
| Temporary overvoltage ($U_T$) – characteristic | 440 V / 120 min. – withstand |
| Leakage current | no leakage current |
| Operating temperature range ($T_U$) | -40 °C … +80 °C |
| Operating state / fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (min.) | 1.5 mm² solid / flexible |
| Cross-sectional area (max.) | 35 mm² stranded / 25 mm² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 2 Standard DIN module, DIN 43880 |
| Approvals | KEMA |
| Type of remote signalling contact | changeover contact |
| Switching capacity (a.c.) | 250 V / 0.5 A |
| Switching capacity (d.c.) | 250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A |
| Cross-sectional area for remote signalling terminals | max. 1.5 mm² solid / flexible |

| **Masterdata** | |
|---|---|
| Net weight | 240.5 g/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85363030 |
| GTIN | 4013364376656 |
| PU | 1 pc(s) |

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.