
DEHNguard modular with Advanced Circuit Interruption (Safe Dimensioning)

DG M TNC ACI 275 FM (952330)

- ACI switch/spark gap combination integrated within the protection module
- Prewired complete unit consisting of a base part and plug-in protection modules
- High device reliability due to „Thermo Dynamic Control“ arrester monitoring and ACI technology
- No backup fuse necessary due to ACI technology
- Small cross-sectional area of 6 mm² always sufficient





Basic circuit diagram

Modular surge arrester with Advanced Circuit Interruption (ACI) for TN-C systems.

Type	DG M TNC ACI 275 FM
Part No.	**952330**
SPD according to EN 61643-11 / IEC 61643-11	type 2 / class II
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_C)	275 V (50 / 60 Hz)
Nominal discharge current (8/20 µs) (I_n)	20 kA
Voltage protection level (U_P)	≤ 1.5 kV
Voltage protection level at 5 kA (U_P)	≤ 1,5 kV
Response time (t_A)	≤ 100 ns
Additional external fuse necessary	not required
Short-circuit withstand capability (I_{SCCR})	25 kA_{rms}
Temporary overvoltage (U_T) – characteristic	440 V / 120 min. – withstand
Leakage current	no leakage current
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm² solid / flexible
Cross-sectional area (max.)	35 mm² stranded / 25 mm² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	3 Standard DIN module, DIN 43880
Approvals	KEMA
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm² solid / flexible

Masterdata	
Net weight	354.26 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363030
GTIN	4013364376649
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.