
DG PCB PV SCI 300 FM (952 753)

- Integration of DEHNguard protection modules in the PCBs of electronic / electrical devices
- Easy and flexible use for all circuit configurations
- Coded base part and protection module ensure against installing an incorrect module





Dimension drawing

Single-pole base for DEHNguard modules to be mounted on the PCBs of devices, with remote signalling contact for monitoring system (floating changeover contact).

Type	**DG PCB PV SCI 300 FM**
Part No.	**952 753**
Associated protection module	DG MOD PV SCI 300 (Part No. 952 053)
Max. continuous operating DC voltage (module)	300 V
Operating temperature range (T_U)	-40 °C ... +80 °C
For mounting on	directly soldered into PCB
Enclosure material	thermoplastic, red, UL 94 V-0
Degree of protection	IP 20 (protection module plugged in)
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	125 V / 0,1 A
Switching capacity (d.c.)	42 V / 0,5 A; 24 V / 1 A; 12 V / 2 A
Remote signalling contact soldering temperature	max. 260 °C / 5 sec.

Masterdata	
Net weight	17.5 g/pc(s)
GTIN	4013364150720
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85366930

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.