


DR M 4P 255 (953 400)

- Four-pole surge arrester consisting of a base element and a plug-in protection module
- High discharge capacity due to heavy-duty zinc oxide varistor / spark gap combination
- Energy coordination with other arresters of the Red/Line product family





Basic circuit diagram



Dimension drawing

Four-pole surge arrester consisting of a base part and a plug-in protection module.

Type	**DR M 4P 255**
Part No.	**953 400**
SPD according to EN 61643-11 / IEC 61643-11	type 3 / class III
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_C)	255 / 440 V (50 / 60 Hz)
Nominal load current (a.c.) (I_L)	25 A
Nominal discharge current (8/20 µs) (I_n)	3 kA
Total discharge current (8/20 µs) [L1+L2+L3+N-PE] (I_{total})	8 kA
Combination wave (U_{OC})	6 kV
Combination wave [L1+L2+L3+N-PE] ($U_{OC\ total}$)	16 kV
Voltage protection level [L-N] / [L/N-PE] (U_p)	≤ 1000 / ≤ 1500 V
Response time [L-N] (t_A)	≤ 25 ns
Response time [L/N-PE] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	25 A gG or B 25 A
Short-circuit withstand capability for mains-side overcurrent protection with 25 A gL/gG (I_{SCCR})	6 kA_{rms}
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	335 V / 5 sec. – Festigkeit 440 V / 120 min. – sicherer Ausfall
Temporary overvoltage (TOV) [L/N-PE] (U_T) – Characteristic	335 V / 120 min. – Festigkeit 440 V / 5 sec. – Festigkeit
Temporary overvoltage (TOV) [N-PE] (U_T) - Characteristic	1200 V / 200 ms – safe failure
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	0.5 mm^2 solid / flexible
Cross-sectional area (max.)	4 mm^2 stranded / 2.5 mm^2 flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Dimensions	2 modules, DIN 43880
Approvals	KEMA, VDE

Masterdata	
Net weight	147.17 g/pc(s)
GTIN	4013364115767
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363030

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component