


DV M2 TN 255 FM (956 205)

- Prewired spark-gap-based type 1, type 2 and type 3 combined arrester consisting of a base part and plug-in protection modules
- Compact unit meets maximum safety requirements thanks to Rapid Arc Control (RAC)
- Capable of protecting terminal equipment





Basic circuit diagram



Dimension drawing

Modular combined lightning current and surge arrester for single-phase TN systems.

Type	DV M2 TN 255 FM
Part No.	**956 205**
SPD according to EN 61643-11 / IEC 61643-11	type 1 + type 2 + type 3 / class I + class II + class III
Energy coordination with terminal equipment (≤ 10 m)	Type 1 + Type 2 + Type 3
Nominal voltage (a.c.) (U_N)	230 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_C)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 µs) [L+N-PE] (I_{total})	50 kA
Specific energy [L+N-PE] (W/R)	625.00 kJ/ohms
Lightning impulse current (10/350 µs) [L, N-PE] (I_{imp})	25 kA
Specific energy [L,N-PE] (W/R)	156.25 kJ/ohms
Nominal discharge current (8/20 µs) [L/N-PE]/[L+N-PE] (I_n)	25 / 50 kA
Voltage protection level [L-PE]/[N-PE] (U_p)	≤ 1.5 / ≤ 1.5 kV
Open-circuit voltage of the combination wave generator (U_{OC})	6 kV
Follow current extinguishing capability (a.c.) (I_{fi})	50 kA_{rms}
Follow current limitation / Selectivity	No tripping of a 35 A gG fuse up to 50 kA_{rms} (prosp.)
Short-circuit current rating [L-N]/[N-PE] (I_{SCCR})	50 kA_{rms}
Response time (t_A)	≤ 100 ns
Max. backup fuse	250 A gG
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	440 V / 120 min. – withstand
Let-through energy in combination with an MOV S20K275 (Iimp = 2.5 ... 25 kA)	< 1 J
Operating temperature range [parallel]/[series] (T_U)	-40 °C ... +80 °C / -40 °C ... +60 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (L, N, PE,) (min.)	6 mm^2 solid / fine-stranded
Cross-sectional area (L, N, PE,) (max.)	35 mm^2 stranded / 25 mm^2 fine-stranded
For mounting on	35 mm DIN rails acc. to EN 60715
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 Standard DIN module, DIN 43880
Approvals	VDE, KEMA, UL
Type of remote signalling contact	yes / changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm^2 solid / fine-stranded
Extended technical data	
Max. prospective short-circuit current	100 kA_{rms} (220 kA_{peak})
Limitation / Extinction of mains follow currents	up to 100 kA_{rms} (220 kA_{peak})
Arrester use at 16.7 Hz – traction power supply systems	
Test voltage AC (U_C)	266 V
Nominal AC voltage (U_N)	230 V

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

Arrester use at 16.7 Hz – traction power supply systems	
Nominal frequency AC (f_N)	16.7 Hz
Max. backup fuse	160 A gG @ 16,7 Hz

Masterdata	
Net weight	271.47 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364510579
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

[1)] See installation instructions for definition of S_2