

DGPM 440 (961 160)

- RADAX Flow spark gap technology
- Discharge capacity of 100 kA (10/350 µs)
- Total current arrester specifically designed for installation in „“3+1““ and „“1+1““ circuits of TT systems according to DIN VDE 0100-534 between neutral conductor N and protective conductor PE





Basic circuit diagram



Dimension drawing

Coordinated single-pole N-PE lightning current arrester for U_C = 440 V.

Type	DGPM 440
Part No.	**961 160**
SPD according to EN 61643-11 / IEC 61643-11	type 1 / class I
Max. continuous operating voltage (AC) (U_C)	440 V (50 / 60 Hz)
Lightning impulse current (10/350 µs) (I_{imp})	100 kA
Specific energy (W/R)	2.50 MJ/ohms
Voltage protection level (U_p)	≤ 2.5 kV
Follow current extinguishing capability (a.c.) (I_{fi})	100 A_{eff}
Response time (t_A)	≤ 100 ns
Temporary overvoltage (TOV)	1200 V / 200 ms
Temporary overvoltage (U_T) – characteristic	1200 V / 200 ms. – withstand
Operating temperature range (parallel connection) (T_{UP})	-40 °C ... +80 °C
Operating temperature range (through-wiring) (T_{US})	-40 °C ... +60 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (N, PE,) (min.)	10 mm^2 solid / flexible
Cross-sectional area (N, PE) (max.)	50 mm^2 stranded / 35 mm^2 flexible
Cross-sectional area () (max.)	35 mm^2 stranded / 25 mm^2 flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 Standard DIN module, DIN 43880
Approvals	UL

Masterdata	
Net weight	369 g/pc(s)
GTIN	4013364116290
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363030

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.