Earthing and short-circuiting device VI, earth clamp with flexible adjustable handle

EKV3 25VI DG V162LDM (V162LDM)



Adjustable handle with two positions, clamping range up to 20 mm.
For cable distribution cabinets.

Type	EKV3 25VI DG V162LDM
Part No.	**V162LDM**
Version	Three-pole
Cable cross-section (phase side)	25 mm²
Cable cross-section (earth side)	25 mm²
Cable cross-section Cu	25/25 mm²
Length of phase cable A	200 mm
Length of phase cable B	400 mm
Length of phase cable C	600 mm
Length of earthing cable	500 mm
Fully insulated	yes
Max. short-circuit current I_k 0.5 s	7.0 kA
Max. short-circuit current I_k 1 s	4.9 kA
Material (clamp body)	**Copper alloy/gal Sn**
Material (sheaths)	**Macrolon**
Temperature range	–25 °C ... +55 °C

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364162655
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component