
# EKV4U0 35 G V93UVAP (V93UVAP)

- Anti-rotation crimped cable lugs (type PK1)
- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator




| Type | EKV4U0 35 G V93UVAP |
|---|---|
| **Part No.** | **V93UVAP** |
| Temperature range | –25 °C … +55 °C |
| Version | Four-pole |
| Cable cross-section (phase side) | 35 mm² |
| Cable cross-section (earth side) | 35 mm² |
| Length of phase cable A | 600 mm |
| Length of phase cable B | 600 mm |
| Length of phase cable C | 600 mm |
| Length of phase cable F | 600 mm |
| Length of earthing cable | 1800 mm |
| Cable cross-section | 35 mm² |
| Fully insulated | No |
| Max. short-circuit current $I_k$ 0.5 s | 10.0 kA |
| Max. short-circuit current $I_k$ 1 s | 6.9 kA |
| Crimped cable lug design | PK1 |
| Standard | EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100) |
| Material (cable) | **E-Cu, extra finely stranded and highly flexible** |
| Material (sheath) | **Thermoplastic polymer (flexible PVC compound YM2)** |
| Hole (cable lug) | Ø12.5 mm |

| Masterdata | |
|---|---|
| Net weight | 2.42 kg/pc(s) |
| GTIN | 4013364164024 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85359000 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component