
EKV1+1 16 VE5E8FZ (VE5E8FZ)



Type	EKV1+1 16 VE5E8FZ
Part No.	**VE5E8FZ**
Phase cable end	PSK 4 30 SQL
Earth cable end	EFK FL40 SKN
Clamping range Ø	4 … 30 mm
Cable cross-section Cu	16 mm²
Max. short-circuit current I_k 0.5 s	4.5 kA
Max. short-circuit current I_k 1 s	3.2 kA
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	–25 °C … +55 °C
Material (cable)	**E-Cu, extra finely stranded and highly flexible**
Material (sheath)	**Thermoplastic (soft PVC compound YM2)**

Masterdata	
Net weight	3.2 kg/pc(s)
GTIN	4013364165557
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component