Earthing and short-circuiting device VI, spring-loaded earth clamp

EKV3 35VI EK VEH4JQY (VEH4JQY)



Clamping range up to 24 mm, installation via adjustable handle DGF EKV VI.
For cable distribution cabinets.

Type	**EKV3 35VI EK VEH4JQY**
Part No.	**VEH4JQY**
Version	Three-pole
Cable cross-section (phase side)	35 mm²
Cable cross-section (earth side)	35 mm²
Cable cross-section Cu	35/35 mm²
Length of phase cable A	200 mm
Length of phase cable B	400 mm
Length of phase cable C	600 mm
Length of earthing cable	500 mm
Fully insulated	yes
Max. short-circuit current I_k 0.5 s	10.0 kA
Max. short-circuit current I_k 1 s	6.9 kA
Material (clamp body)	**Copper alloy/gal Sn**
Material (sheaths)	**Macrolon**
Temperature range	–25 °C … +55 °C

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364163850
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component