# EKV1+0 70 VPZBBSL (VPZBBSL)

- Anti-rotation crimped cable lugs (type PK1)
- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator




| Type | EKV1+0 70 VPZBBSL |
|---|---|
| **Part No.** | **VPZBBSL** |
| Temperature range | –25 °C … +55 °C |
| Version | Single-pole |
| Cable cross-section (phase side) | 70 mm² |
| Cable cross-section (earth side) | 70 mm² |
| Length of single-pole cable | 5000 mm |
| Cable cross-section | 70 mm² |
| Fully insulated | No |
| Max. short-circuit current $I_k$ 0.5 s | 19.5 kA |
| Max. short-circuit current $I_k$ 1 s | 13.8 kA |
| Crimped cable lug design | PK1 |
| Standard | EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100) |
| Material (cable) | **E-Cu, extra finely stranded and highly flexible** |
| Material (sheath) | **Thermoplastic polymer (flexible PVC compound YM2)** |
| Hole (cable lug) | Ø12.5 mm |

| Masterdata | |
|---|---|
| Net weight | 4.03 kg/pc(s) |
| GTIN | 4013364163317 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85359000 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.