Earthing and short-circuiting device TI, earth clamp with flexible adjustable handle

EKV3 35TI DG VSHDQZB (VSHDQZB)



Adjustable handle with two positions, clamping range up to 20 mm.
For cable distribution cabinets.

Type	**EKV3 35TI DG VSHDQZB**
Part No.	**VSHDQZB**
Version	Three-pole
Cable cross-section (phase side)	35 mm²
Cable cross-section (earth side)	35 mm²
Cable cross-section Cu	35/35 mm²
Length of phase cable A	200 mm
Length of phase cable B	400 mm
Length of phase cable C	600 mm
Length of earthing cable	500 mm
Fully insulated	No
Max. short-circuit current I_k 0.5 s	10.0 kA
Max. short-circuit current I_k 1 s	6.9 kA
Connection at the phase conductor	M10 bolt
Material (bolts)	**Copper alloy / gal Sn**
Temperature range	–25 °C … +55 °C

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85359000
GTIN	4013364163836
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Note: When ordering, please specify a clear Variant No.