Anybus X-gateway – DeviceNet Adapter - Modbus RTU Slave



A protocol converter that connects DeviceNet and Modbus RTU control systems

Item number: AB7860-F

The Anybus X-gateway DeviceNet Adapter to Modbus RTU Slave enables you to connect any DeviceNet control system to any Modbus RTU control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.

Features and benefits

- **Reach new markets**
  Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- **Slim hardware design**
  The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- **Easy configuration – No programming required!**
  Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- **Trusted partner**
  Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- **No PLC card slot needed**
  The gateway does not use a card slot in the control system, leaving room for other equipment.
- **3-year warranty**
  The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided
- **Increased PLC performance**
  The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- **Life cycle management**
  HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway – DeviceNet Adapter - Modbus RTU Slave



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	420
Packed Width (mm)	155
Packed Height (mm)	75
Packed Depth (mm)	200
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic

Anybus X-gateway – DeviceNet Adapter - Modbus RTU Slave



General

Packaging Material	Cardboard

Identification and Status

Product ID	AB7860-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	5A991.b.4b

Physical Features

Contains Battery	No

DeviceNet Features

DeviceNet Mode	Adapter / Slave
DeviceNet Configuration File	EDS available
DeviceNet Baud Rate	125-500 kbit/s
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

Modbus-RTU Features

Modbus-RTU Mode	Slave mode
Modbus-RTU Supported Functionality	Modbus-RTU compliant passive slave node operation; 256 Modbus registers in each direction; Modbus diagnostics
Modbus-RTU Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 22, 23
Modbus-RTU Baud Rate	1200bps - 57600bps
Modbus-RTU Input Data Size	512 bytes
Modbus-RTU Output Data Size	512 bytes

Certifications and Standards

Protection Class IP	IP20

Anybus X-gateway – DeviceNet Adapter - Modbus RTU Slave



Certifications and Standards

RoHS Compliant	Yes
Recycle / Disposal	TRUE
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment