# Anybus X-gateway – CC-Link IE Field Slave - Modbus TCP Server

**Item number: AB7958-F**

The Anybus X-gateway CC-Link IE Field Slave to Modbus TCP Server enables you to connect any CC-Link IE Field control system to any Modbus TCP control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.




*A protocol converter that connects CC-Link IE Field and Modbus TCP control systems*

## Features and benefits

**Reach new markets**

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.

**Slim hardware design**

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

**Easy configuration – No programming required!**

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.

**Trusted partner**

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

**No PLC card slot needed**

The gateway does not use a card slot in the control system, leaving room for other equipment.

**3-year warranty**

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided

**Increased PLC performance**

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.

**Life cycle management**

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway – CC-Link IE Field Slave - Modbus TCP Server



## General

| | |
|---|---|
| **Net Width (mm)** | 44 |
| **Net Height (mm)** | 127 |
| **Net Depth (mm)** | 114 |
| **Net Weight (g)** | 420 |
| **Packed Width (mm)** | 155 |
| **Packed Height (mm)** | 75 |
| **Packed Depth (mm)** | 200 |
| **Packed Weight (g)** | 600 |
| **Operating Temperature °C Min** | -25 |
| **Operating Temperature °C Max** | 65 |
| **Storage Temperature °C Min** | -40 |
| **Storage Temperature °C Max** | 85 |
| **Current Consumption Type Value at Vcc Nom (mA)** | 200mA @ 24V DC |
| **Current Consumption Max value at Vcc nom (mA)** | 400mA @ 24V DC |
| **Input Voltage (V)** | 24V DC (-20% to +20%) |
| **Power Connector** | 2-pin, 5.08 Phoenix plug connector |
| **Isolation** | TRUE |
| **Mounting** | DIN-rail (EN 50022 standard) |
| **Housing Materials** | Aluminium, Plastic |

# Anybus X-gateway – CC-Link IE Field Slave - Modbus TCP Server



## General

| | |
|---|---|
| **Packaging Material** | Cardboard |

## Identification and Status

| | |
|---|---|
| **Product ID** | AB7958-F |
| **Country of Origin** | Sweden |
| **HS Code** | 8517620000 |
| **Dual Usage** | No |
| **Export Control Classification Number (ECCN) (Applies only to the U.S)** | 5A991.b.1 |

## Physical Features

| | |
|---|---|
| **Contains Battery** | No |

## CC-Link IE Field Features

| | |
|---|---|
| **CC-Link IE Field Mode** | Slave |
| **CC-Link IE Field Supported Functionality** | CC-Link IE Field Network Intelligent Device Station |
| **CC-Link IE Field Bandwith** | 1 Gbit/s fixed |
| **CC-Link IE Field Input Data Size** | 512 bytes |
| **CC-Link IE Field Output Data Size** | 512 bytes |

## Modbus-TCP Features

| | |
|---|---|
| **Modbus-TCP Mode** | Slave / Server |
| **Modbus-TCP Supported Functionality** | Modbus specification V1.0; Daisy chaining; QoS; Modbus TCP class 0, class 1 and partially class 2 slave functionality |
| **Modbus-TCP Bandwidth** | 10/100 Mbit/s |
| **Modbus-TCP Input Data Size** | 512 bytes |
| **Modbus-TCP Output Data Size** | 512 bytes |

## Certifications and Standards

| | |
|---|---|
| **Protection Class IP** | IP20 |
| **RoHS Compliant** | Yes |

# Anybus X-gateway – CC-Link IE Field Slave - Modbus TCP Server



## Certifications and Standards

| | |
|---|---|
| **Recycle / Disposal** | TRUE |
| **UL Information** | E214107: Ord.Loc UL508, CSA C22.2 NO. 142 |
| **Environment** | EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 |
| **WEEE Category** | IT and telecommunications equipment |