Anybus CompactCom Connector Board - DeviceNet



Item number: AB6664-B

Used together with the CompactCom Brick to get quick and easy access to network connectors.

Network connectors - ready for use together with the CompactCom Brick

Features and benefits

Easy mounting

Incorporates a male strip connector - pluggable and solderable.

Modular

Mix and match CompactCom Bricks and connector boards to give your host application access to different networks.

Robust

Safe and secure mounting of the brick interface to the host PCB design.

Compatible with Starter Kit

Used together with the Anybus CompactCom Starter Kit (Brick version) to get access to the right network connectors.

Anybus CompactCom Connector Board - DeviceNet



General

Net Width (mm)	40
Net Height (mm)	16
Net Depth (mm)	35
Net Weight (g)	10
Packed Width (mm)	8
Packed Height (mm)	3
Packed Depth (mm)	7
Packed Weight (g)	30
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Isolation	Galvanic Isolation
Content of Delivery	Connector board
Not Included (in delivery)	Female strip connector, stand-off spacer
Mounting	PCB mounting via a customized CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6664-B
Country of Origin	Sweden

Anybus CompactCom Connector Board - DeviceNet



Identification and Status

HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	1x 5-pin 5.08 MSTBA
Contains Battery	No

Use Case

