Anybus CompactCom 40 Module Without Housing - CC-Link



Item number: AB6702-C

The Anybus CompactCom 40 Without Housing - CC-Link is a communication interface that can be embedded into any industrial device or machine to enable communication with CC-Link networks. The module version includes connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and CC-Link networks

Features and benefits

High performance

Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.

Quick time to market

HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.

Life cycle management

HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.

Custom look

Delivered without housing, enabling the Anybus CompactCom to be securely integrated behind the front panel of your device, resulting in a customized appearance and seamless design integration.

Supports hardware changes

Possible to swap or install late in the manufacturing process.

Versatile Event-Based Hardware Interfaces

Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.

CLPA pre-certified

Pre-certified with CLPA for network compliance, enabling faster network certification.

Complete communication interface

The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.

Robust Security Measures

Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

Anybus CompactCom 40 Module Without Housing - CC-Link



General

Net Width (mm)	37
Net Height (mm)	16
Net Depth (mm)	51
Net Weight (g)	30
Packed Weight (g)	30
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 50 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 module (without housing)
Mounting	PCB mounting via a CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6702-C
Country of Origin	Sweden

Anybus CompactCom 40 Module Without Housing - CC-Link



Identification and Status

HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	3A991.a.2

Physical Features

Connectors / Input / Output	1x 5-pin 5.08 MSTBA
LED Indicators	Semi-Integrated. RUN and Error via application interface or external light pipes
Form Factor	Module without Housing
Contains Battery	No

CC-Link Features

CC-Link Mode	CC-link Remote Device
CC-Link Supported Functionality	CC-Link v.1.10 (default). CC-Link v.2.00. Automatic CC-Link system handshaking.
CC-Link Configuration File	CSP available
CC-Link Baud Rate	Common Baudrates up to 10 Mbps
CC-Link Output Data Size	368 bytes (CC-Link v.2.00)
CC-Link Input Data Size	368 bytes (CC-Link v.2.00)

Certifications and Standards

RoHS Compliant	Yes
Product Certifications	RoHS, UL
UL Information	E214107