# Anybus CompactCom 40 Module M12 Without Housing - Modbus-TCP



**Item number: AB6743-C**

The Anybus CompactCom 40 M12 Without Housing - Modbus-TCP is a communication interface that can be embedded into any industrial device or machine to enable communication with Modbus-TCP networks. The module version includes network connectors to simplify installation, helping you achieve a fast time to market.

*Enable communication between industrial devices and Modbus-TCP networks*

## Features and benefits

**M12 Connector**

The M12 connectors provides the opportunity to raise the IP rating of a product up to IP67.

**Versatile Event-Based Hardware Interfaces**

Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.

**Modbus pre-certified**

Pre-certified with Modbus for network compliance, enabling faster network certification.

**Complete communication interface**

The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.

**Robust Security Measures**

Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

**High performance**

Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.

**Quick time to market**

HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.

**Life cycle management**

HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.

**Easy to install**

Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.

# Anybus CompactCom 40 Module M12 Without Housing - Modbus-TCP



## General

| | |
|---|---|
| **Net Weight (g)** | 32 |
| **Packed Weight (g)** | 32 |
| **Operating Temperature °C Min** | -40 |
| **Operating Temperature °C Max** | 85 |
| **Storage Temperature °C Min** | -40 |
| **Storage Temperature °C Max** | 85 |
| **Current Consumption Class (CompactCom series)** | B |
| **Current Consumption Max value at Vcc nom (mA)** | up to 500 mA |
| **Input Voltage (V)** | 3.3 VDC, +/- 0.15 VDC |
| **Application Interface** | Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 20 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps). |
| **Isolation** | Galvanic Isolation |
| **Content of Delivery** | CompactCom M40 M12 module |
| **Mounting** | PCB mounting via a CompactFlash connector |
| **Warranty (years)** | 1 year |

## Identification and Status

| | |
|---|---|
| **Product ID** | AB6743-C |
| **Country of Origin** | Sweden |
| **HS Code** | 8517620000 |
| **Dual Usage** | No |
| **Export Control Classification Number (ECCN) (Applies only to the U.S)** | EAR99 |

# Anybus CompactCom 40 Module M12 Without Housing - Modbus-TCP



## Physical Features

| | |
|---|---|
| **Connectors / Input / Output** | 2x M12 |
| **LED Indicators** | Semi-Integrated. Link/Activity are availbe on RJ45 connectors. RUN and Error via application interface or external light pipes |
| **Form Factor** | Module without Housing |
| **Contains Battery** | No |

## Modbus-TCP Features

| | |
|---|---|
| **Modbus-TCP Mode** | Slave/Server |
| **Modbus-TCP Supported Functionality** | Modbus TCP V3.0. Web server w. customizable content. FTP server. Email client. Server Side Include (SSI) functionality. JSON functionality. Transparent Socket Interface. |
| **Modbus-TCP Bandwidth** | 10/100 Mbit/s |
| **Modbus-TCP Input Data Size** | 1536 bytes |
| **Modbus-TCP Output Data Size** | 1536 bytes |

## Certifications and Standards

| | |
|---|---|
| **RoHS Compliant** | Yes |
| **UL Information** | E214107 |