Anybus CompactCom 40 Module M12 Without Housing DeviceNet



Item number: AB6741-C

The Anybus CompactCom 40 M12 Without Housing - DeviceNet is a communication interface that can be embedded into any industrial device or machine to enable communication with DeviceNet networks. The module version includes network connectors to simplify installation, helping you achieve a fast time to market.

Enable communication between industrial devices and DeviceNet networks

Features and benefits

M12 Connector

The M12 connectors provides the opportunity to raise the IP rating of a product up to IP67.

Versatile Event-Based Hardware Interfaces

Enjoy fast and flexible event-based application hardware interfaces with the option to choose from 8/16-bit parallel or high-speed SPI, and I/O via the shift register interface.

ODVA pre-certified

Pre-certified with ODVA for network compliance, enabling faster network certification.

Complete communication interface

The Anybus CompactCom module is a complete communication interface, equipped with connectors that simplify integration. Enjoy an all-in-one solution with easy interchangeability.

Robust Security Measures

Mandatory software signatures prevent unauthorized downloads to the Anybus CompactCom, while robust encryption techniques safeguard against illicit copying.

High performance

Powered by the award-winning NP40 network processor, the Anybus CompactCom guarantees fast data transfer and low latency, making it ideal for the most demanding industrial applications.

Quick time to market

HMS provides comprehensive support throughout the integration journey, ensuring a quick time to market.

Life cycle management

HMS maintains every part of the Anybus CompactCom, including network updates, throughout the product's lifecycle.

Easy to install

Installing the Anybus CompactCom module is a breeze—simply slide it into the host slot. This user-friendly process can be completed by the end-user.

Anybus CompactCom 40 Module M12 Without Housing DeviceNet



General

Net Weight (g)	32
Packed Weight (g)	32
Operating Temperature °C Min	-40
Operating Temperature °C Max	85
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Class (CompactCom series)	B
Current Consumption Max value at Vcc nom (mA)	up to 500 mA
Input Voltage (V)	3.3 VDC, +/- 0.15 VDC
Application Interface	Parallel 8/16-bit (30 ns access). High speed SPI (baudrate configurable up to 20 MHz). Shift register interface (cyclical update time 82 µs). UART (for backwards compatibility with 30-series, max 625kbps).
Isolation	Galvanic Isolation
Content of Delivery	CompactCom M40 M12 module
Mounting	PCB mounting via a CompactFlash connector
Warranty (years)	1 year

Identification and Status

Product ID	AB6741-C
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Anybus CompactCom 40 Module M12 Without Housing DeviceNet



Physical Features

Connectors / Input / Output	2x M12
LED Indicators	Semi-Integrated. Link/Activity are availbe on RJ45 connectors. RUN and Error via application interface or external light pipes
Form Factor	Module without Housing
Contains Battery	No

DeviceNet Features

DeviceNet Mode	Adapter
DeviceNet Supported Functionality	CIP Parameter Object Support. Explicit messaging. UCMM Capable. Bit-strobed I/O. Change-of-state / Cyclic I/O. Polled I/O. Automatic Baud Rate Detection. Quick Connect.
DeviceNet Configuration File	EDS available
DeviceNet Baud Rate	125-500 kbps
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

Certifications and Standards

RoHS Compliant	Yes
UL Information	E214107