Ixxat CAN-IB200/PCIe

Item number: 1.01.0233.11000

The Ixxat CAN-IB200/PCIe is an active PCI Express interface card with one CAN channel. It is an easy and very cost-efficient way to connect computers to a CAN bus network, enabling simple integration into diverse industrial setups, supporting various CAN applications.



PC interface card for CAN (1 x CAN)

Features and benefits

Active CAN interface card

Fulfills even high requirements in data pre-processing, like precise on-board time-stamping and data filtering.

PCIe interface

Single-lane (1x) PCI Express interface supports high-speed data transmission, ideal for demanding industrial applications.

Standard slot bracket

Standard slot bracket size ensures compatibility with a wide range of PC systems.

Comprehensive driver compatibility

Ixxat VCI driver packages support multiple fieldbuses and allow easy switching between different PC interface types. Available as free download.

Analysis software included

Ixxat canAnalyser3 Mini is included in the VCI V4 download package and enables first steps in analyzing and monitoring CAN networks.

Cost-effective connectivity

Offers a cost-effective solution, delivering high performance at an economical price. Ideal choice for demanding applications, without having to compromise on quality.

Use in industrial and standard PCs

PC board with slot plate for fixed installation in desktop or industrial PCs, providing reliable connectivity.

Installation of multiple cards

Integration of multiple cards in one PC allows easy channel extension, making it suitable even for demanding settings like test benches and manufacturing plants.

Powerful programming interface

Ixxat offers versatile programming interfaces for Windows (VCI), Linux (ECI) and real-time OS (on request), enabling flexible development across multiple operating systems.

Ixxat CAN-IB200/PCIe



General

Net Width (mm)	69
Net Height (mm)	105
Net Weight (g)	180
Packed Width (mm)	13
Packed Height (mm)	5
Packed Depth (mm)	17
Packed Weight (g)	190
Operating Temperature °C Min	0
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	10 to 95 %, non-condensing
Current Consumption Type Value at Vcc Nom (mA)	390 mA (3.3 V DC)
Current Consumption Max value at Vcc nom (mA)	550 mA (3.3 V DC)
Input Voltage (V)	3.3 V DC via PCIe socket
Power Connector	PCIe socket (3.3 V / 12 V DC)
Configuration	configuration as PC interface or bridge via Bluetooth connection, usage of a terminal program or the CANblueCon Configuration Tool possible
Content of Delivery	PC interface card, user manual, available as free download: CAN driver VCI, simple CAN monitor "canAnalyser Mini"
Not Included (in delivery)	Comprehensive and powerful driver and software packages are available as free download

Ixxat CAN-IB200/PCIe



General

Mounting	PCI Express
Packaging Material	Cardboard
Warranty (years)	1

Identification and Status

Product ID	1.01.0233.11000
Country of Origin	Germany
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	EAR99

Physical Features

Connectors / Input / Output	1 x D-Sub 9 connector, 1 x PCI express (V1.1), single lane port (x1)
Contains Battery	No

CAN Features

CAN Mode	CAN high-speed (ISO 11898-2)
CAN Transceiver	TI SN65HVD251
CAN Controller	CAN 2.0 A/B
CAN Baud Rate	10 kBit/s to 1 Mbit/s

Certifications and Standards

CE	Yes
FCC	Yes
WEEE Category	IT and telecommunications equipment