Mitsubishi Heavy Industries FD and VRF systems to Modbus RTU Interface

Item number: INMBSMHI001R000

The Mitsubishi Heavy Industries-Modbus interface allows full bidirectional communication between Mitsubishi Heavy Industries FD and VRF systems and Modbus RTU (RS-485) networks. The interface acts as a server device for the installation, accessing all signals from the air conditioner unit. A wired remote controller can also be part of the network.



Mitsubishi Heavy Industries to Modbus RTU - 1 indoor unit

Features and benefits

- **Modbus RTU (EIA-485) server device**
  The interface acts as a Modbus server device through its Modbus RTU (EIA-485 connector) port.
- **Energy savings through a window contact function**
  This function helps minimize costs, as HVAC systems are a major building energy consumer.
- **AC unit control by both the remote and Modbus RTU**
  The AC unit can be simultaneously controlled by the manufacturer's remote controller and Modbus RTU.
- **Multiple mounting options**
  Mounting options include DIN rail, wall, or, in some AC models, even inside the indoor unit.
- **Dual configuration options**
  Configuration is carried out through the interface's onboard DIP switches and the Modbus interface.
- **Total unit control and monitoring from Modbus RTU**
  Through internal variables, running hours counter (for maintenance purposes), and error indication.
- **No external power required**
  The interface is powered directly from the AC unit, so no external power supply is required.

Mitsubishi Heavy Industries FD and VRF systems to Modbus RTU Interface



General

Capacity	1 indoor unit
Net Width (mm)	53
Net Height (mm)	93
Net Depth (mm)	58
Net Weight (g)	140
Packed Width (mm)	135
Packed Height (mm)	85
Packed Depth (mm)	100
Packed Weight (g)	180
Operating Temperature °C Min	0º
Operating Temperature °C Max	60º
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Consumption (W)	1.54
Configuration	DIP Switches
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Mitsubishi Heavy Industries FD & VRF systems
Content of Delivery	Intesis gateway and installation manual.
Housing Materials	Plastic

Mitsubishi Heavy Industries FD and VRF systems to Modbus RTU Interface



General

Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INMBSMHI001R000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features


LED Indicators	Gateway and communication status.
Contains Battery	No

Certifications and Standards

Product Certifications	CE, CB, UKPSTI, UL
WEEE Category	IT and telecommunications equipment

Mitsubishi Heavy Industries FD and VRF systems to Modbus RTU Interface

Use Case



Integration example.