Daikin AC Domestic units to BACnet/IP & MS/TP Interface

Item number: INBACDAI001I000

The Daikin-BACnet interface allows full bidirectional communication between Daikin domestic air conditioner units and BACnet/IP or MS/TP networks. The interface enables BACnet communication via polling or subscription requests (COV), making the indoor unit available through independent BACnet objects.



Daikin to BACnet/IP & MS/TP - 1 indoor unit

Features and benefits

- **Support for BACnet/IP and BACnet MS/TP**
  BACnet/IP (via Ethernet) or BACnet MS/TP (via EIA-485) connection options are supported.
- **IP settings available via a web interface**
  A configuration tool is available via a web interface with IP settings and more information.
- **Occupancy function to allow energy savings**
  Occupancy function that helps reduce costs, as HVAC systems are one of the main energy consumers.
- **AC unit control by remote and BACnet/IP or MS/TP**
  The AC unit can simultaneously be controlled via BACnet/IP or MS/TP and its own remote controller.
- **Configuration from onboard DIP switches**
  The interface configuration is carried out directly through its onboard DIP switches.
- **AC unit data served as fixed BACnet Objects**
  Air conditioning unit properties and functionalities are abstracted into fixed BACnet Objects.
- **Total unit control and monitoring from BACnet**
  Through internal variables, running hours counter (for maintenance purposes), and error indication.
- **No external power required**
  The interface is powered directly from the AC unit, so no external power supply is required.

Daikin AC Domestic units to BACnet/IP & MS/TP Interface



General

Capacity	1 indoor unit
Net Width (mm)	53
Net Height (mm)	93
Net Depth (mm)	58
Net Weight (g)	90
Packed Width (mm)	135
Packed Height (mm)	85
Packed Depth (mm)	100
Packed Weight (g)	130
Operating Temperature °C Min	0º
Operating Temperature °C Max	60º
Storage Temperature °C Min	0
Storage Temperature °C Max	40
Power Consumption (W)	0.72
Configuration	Web Server
Installation Conditions	This gateway is designed to be mounted inside an enclosure. If the unit is mounted outside an enclosure, precautions should always be taken to prevent electrostatic discharge to the unit. When working inside an enclosure (e.g., making adjustments, setting switches, etc.), typical anti-static precautions should always be followed before touching the unit.
AC Model Compatibility	Daikin Residential
Content of Delivery	Intesis gateway, installation manual and AC connection cable.
Housing Materials	Plastic

Daikin AC Domestic units to BACnet/IP & MS/TP Interface



General

Warranty (years)	3 years
Packaging Material	Cardboard

Identification and Status

Product ID	INBACDAI001I000
Country of Origin	Spain
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99


Physical Features

LED Indicators	Gateway and communication status.
Contains Battery	No

Certifications and Standards

Product Certifications	CE, CB, UL, BTL
WEEE Category	IT and telecommunications equipment

Use Case



Integration example.