Anybus ComBricks Fiber Optic

Item number: 101-201510

The Anybus PROFIBUS Fiber Optic module is a unique product that allows long cable distances and a galvanic isolation between devices and segments.



Enable easy network expansion over long distnaces

Features and benefits

Easy network extension over long distances

The Fiber Optic module supports a cable length of 3km

Customizable topology

The module enables the creation of point-to-point, star and bus topologies

Anybus ComBricks Fiber Optic



General

Net Weight (g)	149
Packed Width (mm)	6
Packed Height (mm)	14
Packed Depth (mm)	20
Packed Weight (g)	220
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	360 mA
Current Consumption Max value at Vcc nom (mA)	510 mA
Power Wire Diameter (mm)	< 2.5 mm²
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-201510
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features

Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes

Anybus ComBricks Fiber Optic



Certifications and Standards

CE	Yes
FCC	Yes
UL	Yes
Waste Certification (WEEE)	No
WEEE Category	IT and telecommunications equipment