Anybus ComBricks Head Station 1C

Item number: 101-20011C

The Head Station Type 1C is an enhanced type that contain a ProfiTrace core for monitoring 4 PROFIBUS networks and an advanced web server for permanent remote maintenance of the PROFIBUS installation over Ethernet



The primary element of the ComBricks modular system

Features and benefits

The main power source for all

The Head Station provides power to all modules through its redundant power supply.

Supporting multiple networks

Repeater modules can be set to 4 network and have integrated scopeware functionalities

Remote web server access

Have full data insight into your network measurements such as status of all devices, live lists, statistics, message recordings, PROFIBUS events and more whenever you need it.

Anybus ComBricks Head Station 1C



General

Net Weight (g)	447
Packed Width (mm)	10
Packed Height (mm)	15
Packed Depth (mm)	20
Packed Weight (g)	697
Operating Temperature °C Min	-20
Operating Temperature °C Max	60
Current Consumption Type Value at Vcc Nom (mA)	73 mA
Current Consumption Max value at Vcc nom (mA)	800 mA
Input Voltage (V)	11…26 VDC
Power Wire Diameter (mm)	< 2.5 mm²
Reverse Polarity Protection	Yes
Mounting	DIN rail mount (bracket included)
Housing Materials	Plastic
Packaging Material	Cardboard
Warranty (years)	1 Year

Identification and Status

Product ID	101-20011C
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features

SD Card Slot	SD

Anybus ComBricks Head Station 1C



Physical Features

Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
CE	Yes
FCC	Yes
UL	Yes
Waste Certification (WEEE)	No
WEEE Category	IT and telecommunications equipment