
Anybus ProfiHub B4FOR+ (Multi-Mode)

Item number: 17430

The ProfiHub B4FOR+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa allowing ring topologies.



Redundant network expansion over long distances

Features and benefits

- **One fiber opitc channel, divided into 2 ports**
  Allowing creation for additional redundancy on the ring
- **Ring redundancy**
  Strenghten the backbone of your network by creating additional redundancy via a ring topology
- **4 galvanically isoltated channels**
  Avoid daisy chained network interruptions

Anybus ProfiHub B4FOR+ (Multi-Mode)



General

Net Width (mm)	111
Net Height (mm)	167
Net Depth (mm)	40
Net Weight (g)	713
Packed Width (mm)	13
Packed Height (mm)	20
Packed Depth (mm)	24
Packed Weight (g)	816
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	250 mA
Current Consumption Max value at Vcc nom (mA)	250 mA
Input Voltage (V)	9...31 VDC
Power Wire Diameter (mm)	< 2.5 mm^2
Reverse Polarity Protection	Yes
Warranty (years)	1 Year

Identification and Status

Product ID	17430
Country of Origin	Netherlands (the)
HS Code	8471800000

Anybus ProfiHub B4FOR+ (Multi-Mode)



Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features

Contains Battery	No

Certifications and Standards

Protection Class IP	IP20
CE	Yes
FCC	Yes
UL	Yes
DNV	No
Waste Certification (WEEE)	No
WEEE Category	IT and telecommunications equipment