
CARLO GAVAZZI
Automation Components

CARLO GAVAZZI



2-pole solid state relays

Switches

RA2A, RK series

2-pole solid state relays

Space costs money! Reducing the size of equipment is becoming a necessity for equipment manufacturers who want to stay competitive. Carlo Gavazzi aligned its product offering accordingly and provide solutions that minimise space requirements without compromising performance.

Amongst these solutions are 2-pole solid state relays that have two outputs which can be either independently or commonly controlled, packaged in one housing providing up to 50% space savings.

The **RA2A** series covers ratings up to 40 AAC per pole and is equipped with FASTON terminations whilst the **RK** series is a more advanced version using the latest design and assembly technology covering ratings up to 75 AAC per pole and is equipped with screw terminations.



Space optimisation solutions

Space savings
- Up to 50% space savings for 2-poles
- Economy switching of 3-phase loads using 2-poles

Time savings in installation
- FASTONs for low current loads (RA2)
- Spring plug for control termination (RK..P)

Long lifetime
- Robust solution with back-to-back thyristor technology instead of triacs
- No internal moulding mass to reduce thermal stresses
- Wire bonding on power chips to reduce thermal and mechanical stresses (RK)

Efficient heat dissipation
- Optimal thermal efficiency by design - low junction temperature due to the low junction to heatsink thermal resistance (RK)


Certifications and conformance
- Certified to International standards
- 100,000 cycle test according UL requirements for Food equipment (RK)
- Conformance to glow wire requirements for Food equipment according to EN 60335 (RK)

One stop shop
- A range of Accessories including heatsinks and cables for a complete package from one supplier

CARLO GAVAZZI Automation Components. Specifications are subject to change without notice. Illustrations are for example only.

Plastic & rubber

- Injection machines
- Thermoforming machines
- Temperature control units
- Dryers



Food & beverage

- Electrical ovens
- Fryers
- Griddles
- Coffee machines



Product range overview






Series	RA2A	RA2A...C	RK...C	RK...P
Current ratings	2x 25 A, 40 A	2x 25 A, 40 A	2x 50 A, 75 A	2x 50 A, 75 A
Max. operating voltage	660 VAC	660 VAC	660 VAC	660 VAC
Power connection	FASTON 6.35mm	FASTON 6.35mm	Screw	Screw
Control connection	FASTON 6.35mm	2.54mm pitch header	2.54mm pitch header	spring plug (provided)
Variants	Dual output with independent control		Dual output with independent or common control	
Switching mode	Zero cross	Zero cross	Zero cross	Zero cross or Instant on
Control ON LED indication (x2)	■	■	■	■
DC control voltage	■	■	■	■
Integrated overvoltage protection	-	Varistor	Transil	Transil
Dimensions W x H x D mm	45 x 58 x 32	45 x 58 x 35	45 x 58 x 33	45 x 58 x 44
Approvals				


RA2A series

2-pole solid state relays

The **RA2A** series consists of solid state relays having 2 outputs independently controlled packaged in a housing having a maximum width of 45mm. This gives a maximum 50% space saving in control panels when compared to 2x standard 1-pole solid state relays.

The **RA2A** is equipped with FASTON terminals on both input and output for time savings in installations. The **RA2A..C** variants are also equipped with FASTONs on the output but the control termination consists of a 2.54mm pitch header.

Ratings go up to 660 VAC, 40 A. The **RA2A** is ideally suited for resistive loads, and the **RA2A..M** is specifically designed for inductive loads.



Fast installation with quick connect terminals

Applications

In some cases, the application conditions will necessitate that the solid state relay is mounted on a heatsink in order to keep the junction temperature of the solid state relay from exceeding its maximum rating.

The size of heatsink required can be determined either from the product datasheets or by making use of the online Heatsink Selector Tool available at:
http://www.gavazziautomation.com/en-gb/products/solid-state-relays/heatsink-selector-tool

Carlo Gavazzi offers a range of heatsinks that can be provided with a pre-mounted solid state relay. Consult a Carlo Gavazzi representative for further details regarding these assemblies.



CARLO GAVAZZI Automation Components. Specifications are subject to change without notice. Illustrations are for example only.

Main features

Fast installation
Quick connect terminals (FASTONs)




User friendly
2x green LEDs for control ON indication




Long lifetime
Free of moulding mass to ensure components are not subject to thermal and mechanical stresses

Compact
2 independently controlled poles in 1 housing

Versatile
RA2A for resistive loads
RA2A..M for inductive loads






Approvals

Approvals



Reliable
Integrated overvoltage protection for **RA2A..C**

Control termination
6.35mm FASTONs for **RA2A**



Control termination
2.54mm pitch header for **RA2A..C**

Selection guide

RA2A series - 2 independently controlled poles for resistive loads

Control termination	Max. current	Control voltage	Operational voltage		
			24-265 VAC	42-530 VAC	42-660 VAC
Fastons	2 x 25 AAC	4.5 - 32 VDC	RA2A23D25	RA2A48D25	RA2A60D25
	2 x 40 AAC	4.5 - 32 VDC	RA2A23D40	RA2A48D40	RA2A60D40
Pins	2 x 25 AAC	4.5 - 32 VDC	RA2A23D25C	-	RA2A60D25C
	2 x 40 AAC	4.5 - 32 VDC	RA2A23D40C	-	RA2A60D40C

RA2A..M series - 2 independently controlled poles for inductive loads

Control termination	Max. current	Control voltage	Operational voltage		
			24-265 VAC	42-530 VAC	42-660 VAC
Fastons	2 x 25 AAC	4.5 - 32 VDC	RA2A23D25M	RA2A48D25M	RA2A60D25M
	2 x 40 AAC	4.5 - 32 VDC	RA2A23D40M	RA2A48D40M	RA2A60D40M


Further details are available on online datasheets at www.gavazziautomation.com

RK series
2-pole solid state relays

The **RK** series also consists of solid state relays with 2 outputs packaged in a platform having a maximum product width of 45mm. However, the **RK** series is dedicated for high rated loads up to 660 VAC, 75 A and hence termination for power connection consists of screw terminals.


The **RK..P** is equipped with a spring plug for control connection that is provided with the solid state relay whilst the **RK..C** is equipped with a 2.54mm pitch header.

The **RK** series consists of 2 variants:
the **RKD2** series has an independent control for each of the poles, the **RK2** series has common control for the 2 poles making it ideal for economy switching of 3-phase loads.




Screw output termination for high power

Applications



The two loads can be controlled independently with the **RKD2 series**




Economy switching of a 3-phase load with the **RK2 series**


CARLO GAVAZZI Automation Components. Specifications are subject to change without notice. Illustrations are for example only.

Main features

Easy replacement
Pluggable control termination




Flexible connections
Removable touch protection cover for connection of ring lugs






Long lifetime
Wire bonding technology for lower thermal and mechanical stresses on power chips



Time saving
Pre-attached thermal interface to backplate





User friendly 2x green LEDs for control ON indication

Low downtime
Integrated overvoltage protection

Space savings
2 poles in a 45mm wide housing **RKD2** for independent control **RK2** for common control

Conformance to Food Industry
UL certified for 100,000 cycle test, Conforms to glow wire requirements of EN 60335

Selection guide

RKD2 series - 2 independently controlled poles

Control termination	Max. current	I²t	Control voltage	Operational voltage	
				24 - 265 VAC	42 - 660 VAC
Pins	2x 50 AAC	1500 A²s	4 - 32 VDC	RKD2A23D50C	RKD2A60D50C
	2x 50 AAC	3000 A²s	4 - 32 VDC	-	RKD2A60D51C
	2x 75 AAC	9800 A²s	4 - 32 VDC	-	RKD2A60D75C
Spring plug	2x 50 AAC	1500 A²s	4 - 32 VDC	RKD2A23D50P	RKD2A60D50P
	2x 50 AAC	3000 A²s	4 - 32 VDC	-	RKD2A60D51P
	2x 75 AAC	9800 A²s	4 - 32 VDC	-	RKD2A60D75P

RK2 series - common control for the 2 poles

Control termination	Max. current	I²t	Control voltage	Operational voltage	
				24 - 265 VAC	42 - 660 VAC
Pins	2x 50 AAC	1500 A²s	4 - 32 VDC	-	RK2A60D50C
	2x 75 AAC	9800 A²s	4 - 32 VDC	-	RK2A60D75C
Spring plug	2x 50 AAC	1500 A²s	4 - 32 VDC	-	RK2A60D50P
	2x 75 AAC	9800 A²s	4 - 32 VDC	-	RK2A60D75P

Instant on versions are also available for 600 VAC: RKD2B60..P, RK2B60..P
Further details are available on online datasheets at www.gavazziautomation.com

CARLO GAVAZZI
Automation Components

CARLO GAVAZZI

OUR SALES NETWORK IN EUROPE

AUSTRIA
Carlo Gavazzi GmbH
Ketzergasse 374,
A-1230 Wient
Tel. +43 1 888 4112
Fax +43 1 889 1053
office@carlogavazzi.at

FINLAND
Carlo Gavazzi OY AB
Ahventie, 4 B
FI-02170 Espoo
Tel. +358 9 756 2000
myynti@gavazzi.fi

GREAT BRITAIN
Carlo Gavazzi UK Ltd
4.4 Frimley Business Park,
Frimley, Camberley,
Surrey GU16 7SG
Tel. +44 1 276 854110
sales@carlogavazzi.co.uk

NORWAY
Carlo Gavazzi AS
Melkeveien 13,
N-3919 Porsgrunn
Tel. +47 35 93 08 00
post@gavazzi.no

SWEDEN
Carlo Gavazzi AB
V:a Kyrkogatan 1,
S-652 24 Karlstad
Tel. +46 54 85 11 25
Fax +46 54 85 11 77
info@carlogavazzi.se

BELGIUM
Carlo Gavazzi NV/SA
Mechelsesteenweg 311,
B-1800 Vilvoorde
Tel. +32 2 257 41 20
sales@carlogavazzi.be

FRANCE
Carlo Gavazzi Sarl
Zac de Paris Nord II, 69,
rue de la Belle Etoile,
F-95956 Roissy CDG Cedex
Tel. +33 1 49 38 98 60
Fax +33 1 48 63 27 43
french.team@carlogavazzi.fr

ITALY
Carlo Gavazzi SpA
Via Milano 13,
I-20045 Lainate (MI)
Tel. +39 02 931 76 1
info@gavazziacbu.it

PORTUGAL
Carlo Gavazzi Lda
Rua dos Jerónimos 38-B,
P-1400-212 Lisboa
Tel. +351 21 361 70 60
Fax +351 21 362 13 73
carlogavazzi@carlogavazzi.pt

SWITZERLAND
Carlo Gavazzi AG
Verkauf Schweiz/Vente Suisse
Sumpfstrasse 3,
CH-6312 Steinhausen
Tel. +41 41 747 45 35
Fax +41 41 740 45 40
info@carlogavazzi.ch

DENMARK
Carlo Gavazzi Handel A/S
Over Hadstenvej 40,
DK-8370 Hadsten
Tel. +45 89 60 61 00
Fax +45 86 98 15 30
handel@gavazzi.dk

GERMANY
Carlo Gavazzi GmbH
Pfnorstr. 10-14
D-64293 Darmstadt
Tel. +49 6151 81 00 0
Fax +49 6151 81 00 40
info@gavazzi.de

NETHERLANDS
Carlo Gavazzi BV
Wijkermeerweg 23,
NL-1948 NT Beverwijk
Tel. +31 251 22 93 45
info@carlogavazzi.nl

SPAIN
Carlo Gavazzi SA
Avda. Iparraguirre, 80-82,
E-48940 Leioa (Bizkaia)
Tel. +34 94 480 40 37
Fax +34 94 431 60 81
gavazzi@gavazzi.es

OUR SALES NETWORK IN THE AMERICAS

USA
Carlo Gavazzi Inc.
750 Hastings Lane,
Buffalo Grove, IL 60089-6904,
USA
Tel. +1 847 465 61 00
sales@carlogavazzi.com

CANADA
Carlo Gavazzi Inc.
2430 Meadowpine Bvd Unit 104
Mississauga, ON L5N 6S2,
Canada
Tel. +1 905 542 0979
gavazzi@carlogavazzi.com

MEXICO
Carlo Gavazzi Mexico S.A. de C.V.
Circuito Puericultores 22,
Ciudad Satelite
Naucalpan de Juárez,
Edo Mex. CP 53100 - Mexico
Tel. +52 55 5373 7042
Fax +52 55 5373 7042
mexicosales@carlogavazzi.com

BRAZIL
Carlo Gavazzi Automação Ltda.
Av. Francisco Matarazzo,
1752 Conjunto 2108
CEP 05001-200 -
São Paulo - SP - Brazil
Tel. +55 11 3052 0832
Fax +55 11 3057 1753
info@carlogavazzi.com.br

OUR SALES NETWORK IN ASIA AND PACIFIC

SINGAPORE
Carlo Gavazzi Automation
Singapore Pte. Ltd.
61 Tai Seng Avenue #05-06
Print Media Hub @ Paya Lebar
iPark
Singapore 534167
Tel. +65 67 466 990
Fax +65 67 461 980
info@carlogavazzi.com.sg

TAIWAN
Branch of Carlo Gavazzi
Automation Singapore Pte. Ltd.
12F-3, No. 530, Yingcai Rd.,
West Dist., Taichung City 403518,
Taiwan, China
Tel. +886 4 2258 4001
Fax +886 4 2258 4002

MALAYSIA
Carlo Gavazzi Automation (M)
SDN. BHD.
D12-06-G, Block D12,
Pusat Perdagangan Dana 1,
Jalan PJU 1A/46,
47301 - Petaling Jaya,
Selangor, Malaysia
Tel. +60 3 7842 7299
Fax +60 3 7842 7399
info@gavazzi-asia.com

CHINA
Carlo Gavazzi Automation
(China) Co. Ltd.
Unit 2308, 23/F.,
News Building, Block 1,1002
Middle Shennan Zhong Road,
Futian District,
Shenzhen, China
Tel. +86 755 8369 9500
Fax +86 755 8369 9300
info@carlogavazzi.cn

INDIA
Carlo Gavazzi Automation
India PVT LTD.
1105/06, Kamdhenu 23 West,
Thane Belapur Road,
TTC Industrial Area
Kopar Khairane, Navi Mumbai
400709, India
Tel. +91 88282 84033
info@carlogavazzi.in

OUR COMPETENCE CENTRES AND PRODUCTION SITES

DENMARK
Carlo Gavazzi Industri A/S
Hadsten

ITALY
Carlo Gavazzi Controls SpA
Belluno

LITHUANIA
Uab Carlo Gavazzi Industri
Kaunas
Kaunas

MALTA
Carlo Gavazzi Ltd
Zejtun

CHINA
Carlo Gavazzi Automation
(Kunshan) Co., Ltd.
Kunshan

MEXICO
Carlo Gavazzi Americas Inc.
Tijuana

HEADQUARTERS

CARLO GAVAZZI AUTOMATION SPA
Via Milano, 13
I-20045 - Lainate (MI) - ITALY
Tel. +39 02 931 761
info@gavazziautomation.com

Energy to Components!

www.gavazziautomation.com

BRO 2POLE SSR ENG 02/26
Specifications are subject to change without notice. Illustrations are for example only.