UL Product iQ®

Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our Historical View FAQs or contact our Customer Service.

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at https://www.ul.com/about/locations.

Switches, Industrial Control - Component

See General Information for Switches, Industrial Control - Component

CARLO GAVAZZI LTD E80573
BLB042
BULEBEL INDUSTRIAL ESTATE
ZEJTUN, ZTN 3000 MALTA

Investigated to ANSI/UL 508

Accessory: relay sockets Model(s) ZPYS2G

Accessory:relay sockets Model(s) ZPYS1G

Industrial applications, open type Model(s) RSLM001012, RSLM001024, RSLM001048, RSLM001060, RSLM100012, RSLM100024, RSLM100048, RSLM100060

Industrial Control Switches, "RMD Series" Model(s) RMD followed by 2 or 3, followed by H, followed by 24 or 48, followed by LA, MA or HA, followed by 30 or 40, may be followed by suffixes.

Industrial Control Switches Model(s) RA and RE followed by 24, 40, 48 or 60, followed by 10, 25, 50, 90, 110, followed by D, LD, HA, A or AA, may be followed by 6, 8, 12 or 16, may be followed by F, may be followed by S18, may be followed by additional suffixes, may be followed by # (as last digit).

RA followed by 12, 23, 40, or 48, followed by 10, 25, 50, 90 or 110, followed by L or H, followed by 6 or 10 or 12 or 16, followed by NO, NC, PO, or PC, may be followed by S, may be followed by F, may be followed by S18, S00, figures or blank, may be followed by # (as last digit).

RA followed by 2 followed by A or B, followed by 23, 40, 48 or 60, followed by AA, AB or D, followed by 25 or 40, may be followed by M, may be followed by S378 or four alphanumeric digits, may be followed by # (as last digit) OR followed by 2 followed by A or B, followed by 23, 40, 48 or 60, followed by D, followed by 25 or 40, followed by C, may be followed by H53, may be followed by suffixes, may be followed by # (as last digit)

RAM1 followed by A or B, followed by 23, 40 or 48, followed by D, LA, A1 -, A 2- or A4 -, followed by 10, may be followed by C4, may be followed by suffixes, may be followed by # (as last digit) OR followed by A or B, followed by 23, 40, 48 or 60, followed by A or D, followed by 25, 50, 51, 75, 100 or 125, may be followed by Z, may be followed by C4 (option limited to load current of max 100A), may be followed by S52, S18 or S378, may be followed by suffixes, may be followed by # (as last digit) OR followed by A or B, followed by 23, 40, 48 or 60, followed by A or D, followed by 25 or 50, may be followed by Z, may be followed by C4, followed by S223, may be followed by suffixes (digit # is not allowed).

RFM followed by 1, followed by A or B, followed by 23, 40, 48 or 60, followed by MBT, followed by 10, 25, 30, 50, may be followed by CV, may be followed by X, may be followed by suffixes (figures and numbers)

RJ1 followed by A or B, followed by 23 or 60, followed by A or D, followed by 40, 45, 50, 70, 75 or 90, may be followed by suffixes U or E, may be followed by P or blank, may be followed by V, T or blank, may be followed by figures or blank, may be followed by S112, may be followed by # (as last digit) OR followed by A or B, followed by 23 or 60, followed by A or D, followed by 20 or 30, may be followed by suffixes U or E, may be followed by P or blank, may be followed by V, T or blank, may be followed by figures or blank, may be followed by S112, may be followed by # (as last digit).

RJ2 followed by A or B, followed by 22, 40, 48 or 60, followed by D or A, followed by 25, 32 or 36, may be followed by E or U, may be followed by P, may be followed by V, may be followed by xxxx (figures and numbers), blank or S112, may be followed by # (as last digit). OR followed by A or B, followed by 22 or 40, followed by D, followed by 25, followed by E or U, may be followed by xxxx (figures and numbers), blank or S112, may be followed by # (as last digit).

RJ3 followed by A or B, followed by 22, 40, 48 or 60, followed by D or A, followed by 20, 25 or 32, may be followed by E or U, may be followed by P, may be followed by V, may be followed by xxxx (figures and numbers), blank or S112, may be followed by # (as last digit).

RJCS may be followed by R, followed by 1, followed by A or B, followed by 23, 40, 48 or 60, followed by D, followed by 20, 30, 50 or 75, may be followed by E, may be followed by P, may be followed by PO, PC, NC, NO, may be followed by S197 (option for model RJCSR1xxD50 only), may be followed by xxxx (figures and numbers).

RJD2 followed by A or B, followed by 23 or 60, followed by D, followed by 30 or 45, may be followed by E, may be followed by xxxx (figures and numbers) or blank, may be followed by S112.

RJT3 followed by A or B, followed by 23, 40, 48 or 60, followed by D, followed by 20 or 25, may be followed by E, may be followed by xxxx (figures and numbers), blank or S112, may be followed by # (as last digit).

RM1 followed by A or B, followed by 23, 40, 48 or 60, followed by D, A, M, A1-, A2- or A4-, followed by 25, 50, 50-M, 75 or 100,may be followed by C4, may be followed by S52, S18 or S378, may be followed by suffixes, may be followed by # (as last digit). OR followed by E, followed by 23, 40, 48 or 60, followed by AA or V, followed by 25, 50, 75, 100 or 125A, may be followed by C4 (option limited to load current of max 100 A), may be followed by S52 or S18, may be followed by suffixes, may be followed by # (as last digit). OR followed by A or B, followed by 23, 40, 48 or 60, followed by D, followed by 25, 50, 75 or 100, followed by L, may be followed by S52 or S18, may be followed by suffixes,may be followed by # (as last digit). OR followed by A or, B, followed by 23, 40, 48 or 60, followed by D, A, M, A1-, A2- or A4-, followed by 10 or 30, may be followed by C4, may be followed by suffixes, may be followed by # (as last digit). OR followed by C, followed by 23, 40, 48 or 60, followed by D, followed by 25, 50, 75, 100 or 125A, may be followed by C4 (option limited to load current of max. 100 A), may be followed by S52 or S18, may be followed by suffixes, may be followed by # (as last digit). OR followed by E, followed by 23, 40, 48 or 60, followed by V, followed by 25, 50, 75, 100, followed by S293 or S293A, may be followed by suffixes, may be followed by # (as last digit).

RM1D060D10 may be followed by "Blank" or by suffixes.

RM1D060D100 may be followed by "Blank" or by suffixes.

RM1D060D20 may be followed by "Blank" or by suffixes.

RM1D060D50 may be followed by "Blank" or by suffixes.

RM1D200D20 may be followed by "Blank" or by suffixes

RM1D200D30 may be followed by "Blank" or by suffixes

RM1D200D50 may be followed by "Blank" or by suffixes

RM1D500D10 may be followed by "Blank" or by suffixes

RN followed by 1 or 2, followed by A, B or L, followed 23, 40 or 48, followed by A, or D, followed by 25, 30, 50, 51 or 63, may be followed by S20, may be followed by additional suffixes OR followed by 3, followed by A, followed by 22, 40 or 48, followed by D, followed by 15 or 30, may be followed by S20, may be followed by additional suffixes OR followed by 1, followed by L, followed by 12, 23, 40 or 48, followed by M, followed by 25, may be followed by S20, may be followed by additional suffixes OR followed by 1, followed by S, followed by 12, 23, 40 or 48, followed by H or L, followed by 30 or 50, followed by NC, NO, PC or PO, may be followed by S20, may be followed by additional suffixes OR followed by 1 or 2, followed by F, followed by 12, 23 or 48, followed by V or I, followed by 30 or 50, may be followed by S20, may be followed by additional suffixes, may be followed by # (as last digit).

RN followed by 1, followed by A or B, followed by 23, 48 or 60, followed by A or D, followed by 10 or 20, followed by E or U.

RP followed by 130, followed by 240 or 440, followed by 3 or 5, followed by 5, 12 or 24.

RP1 followed by A or B followed by 23, 40 or 48 followed by D or A, followed by 3, 5 or 6, may be followed by suffix OR followed by A or B, followed by 23, 40, 48 or 60, followed by D10, may be followed by additional suffixes, may be followed by S40 OR followed by D, followed by 060 or 350, followed by D, followed by 1, 4 or 8, may be followed by additional suffixes, may be followed by Mx.

RS1 followed by A or B, followed by 23, 40 or 48, followed by D or LA or A1- or A2- or A4-,followed by 10, 25 or 40, may be followed by C4, may be followed by S52, may be followed by suffixes, may be followed by #(as last digit) OR followed by A or B, followed by 23, 40 or 48, followed by D or A, followed by 10, 25 or 40, followed by E, may be followed by C4, may be followed by suffixes, may be followed by # (as last digit)

RS1 followed by A or B, followed by 23, 40 or 48, followed by D or LA or A1- or A2- or A4-,followed by 10, 25 or 40, may be followed by C4, may be followed by S52, may be followed by suffixes,may be followed by #(as last digit) OR followed by A or B, followed by 23, 40 or 48, followed by D or A, followed by 10, 25 or 40, followed by E, may be followed by C4, may be followed by suffixes, may be followed by # (as last digit).

RZ or RY followed by 24, 40, 48 or 60, followed by 10, 25, 40 or 55, followed by HA or HD, followed by P or U, followed by 0, 1, 2 or 3.

RZ3 followed by A or B, followed by 40, 48 or 60, followed by LD, D or A, followed by 25, 40, 55 or 75, followed by blank or P, may be followed by # (as last digit).

Open Type Solid State Contactors Model(s) RF followed by 1, followed by A or B, followed by 23, followed by L, M or D, followed by 25, maybe followed by suffixes.

Open type solid state relays for industrial use Model(s) RA4425-D08

Open type, for use in industrial applications Model(s) RPYS001012D, RPYS001012DL, RPYS001012DLT, RPYS001012DT, RPYS001024A, RPYS001024AL, RPYS001024ALT, RPYS001024AT, RPYS001024D, RPYS001024DL, RPYS001024DLT, RPYS001024DT, RPYS001115A, RPYS001115AL, RPYS001115ALT, RPYS001115AT, RPYS001230A, RPYS001230AL, RPYS001230ALT, RPYS001230AT, RPYS002012D, RPYS002012DL, RPYS002012DLT, RPYS002012DT, RPYS002024A, RPYS002024AL, RPYS002024ALT, RPYS002024AT, RPYS002024D, RPYS002024DL, RPYS002024DLT, RPYS002024DT, RPYS002115A, RPYS002115AL, RPYS002115ALT, RPYS002115AT, RPYS002230A, RPYS002230AL, RPYS002230ALT, RPYS002230AT

Relay sockets Model(s) ZD 35/2A, ZD 35/3A, ZD 50/2A, ZD 50/3A, ZMI 2NA, ZMI 2SA, ZMI 3SA, ZMI 4NA, ZMI 4SA

Sockets Model(s) ZPY08A, ZPY11A, ZPY14A

Solid State Relay Model(s) RA2325HD06SS01

RP followed by 1, followed by 0, 1, 2 or 3, followed by 0, 1, or 2, followed by 240 or 440, followed by 0.5, 2 or 4, followed by -0 or -5.

Solid state relay solitrons Model(s) RLSSZ230D2

Solid State Relays Model(s) A, B or C followed by 1 or 2, followed by 01 or 08, followed by 024, 120 or 220, may or may not be followed by 006, 060 or 600

C followed by 1 or 2, followed by 11 or 18, followed by 024, 120 or 220, may or may not be followed by 006, 060 or 600.

RA followed by 24 or 48, followed by 90, followed by LD or HD, followed by 06, 10 or 12.

RA followed by 24, followed by 10, 25 or 40, followed by D or HA, followed by 06, followed by T, may be followed by F, may be followed by additional suffixes and numbers, may be followed by "#" (as last digit).

RA or RB followed by 24, 40, 44 or 48, followed by 10, 25, 50 or 90, followed by HA, HD, LA, D, FO, followed by 06, 08, 10 or 12, may be followed by S, L or LF, may be followed by suffixes and numbers, may be followed by # (as last digit).

RAP followed by 40 or 48, followed by A followed by 3 or 5.

RC followed by 24 or 44, followed by 10, 25 or 50, followed by D, followed by 06 or 12.

Solid state relays Model(s) RJ followed by 1, followed by P, followed by 23, 40, 48 or 60, followed by MBT or MBF, followed by 50, may be followed by E, may be followed by BC, CS or CV, may be followed by suffixes (figures and numbers).

RJ followed by 1, followed by P, followed by 23, 48 or 60, followed by V or I, followed by 30, 50, 70 or 75, may be followed by E, may be followed by PNO or PPO, may be followed by S155 or xxxx (figures and numbers).

RJ2 followed by A or B, followed by 22, 40 or 48, followed by D, followed by 12 or 18, may be followed by E, may be followed by xxxx (figures and numbers), may be followed by # (as last digit).

RK followed by D, followed by 2, followed by A or B, followed by 23, 40, 48 or 60, followed by D, followed by 25, 50, 51 or 75 followed by C or P, may be followed by L, may be followed by suffixes.

Solid State Relays Model(s) RR2 or RR3 followed by I, followed by 40, 48, or 60, followed by 5, 10, 15, 25, 30, or 50, followed by HD, LA, or HA, followed by P.

Solid state relays Model(s) RX followed by 1, followed by A or B, followed by 23, 40 or 48, followed by D or A, followed by 25 or 32, may be followed by V or M, may be followed by F, C or P, may be followed by HT, H20, H0, H4, H15, H21, H5, H3, H6, H16, H7, H17, H2, H18, H19, H13, H10 or H12, may be followed by xxxx or blank (figures and numbers), may be followed by S112, may be followed by # (as last digit) OR followed by 1, followed by A or B, followed by 23, 40 or 48, followed by D or A, followed by 51, may be followed by V or M, may be followed by F, C or P, may be followed by HT, H20, H0, H21, H5, H16, H2, H19, H13, H10 or H12, may be followed by xxxx or blank (figures and numbers), may be followed by S112, may be followed by # (as last digit).

Solid State Relays Model(s) U followed by A0, B0, C0 or C1, or ABC, followed by 5 or 07, followed by 120, 220, 900 or 924, followed by 6, 60 or 600.

Switches industrial control - Hybrid relays Model(s) RMD followed by 1, followed by H, followed by 23, followed by D or A, followed by 20, may be followed by xxxx (figures and numbers) or blank.

Switches industrial controls Model(s) NBD100 12, NBD200 12, NFA100 220F, NFA200 220F, RMI-2, RMI-3, RMI-4

Investigated to

Industrial Control Switches Model(s) Cat.Nos. RAM1 followed by A or B, followed by 23, 40, 48 or 60, followed by A or D, followed by 25 or 50, may be followed by Z, may be followed by C4, followed by S223, may be followed by suffixes (digit "#" is not allowed).

NB followed by D or A, followed by 100 or 200, followed by coil voltage, followed by F or FE or S or SE or SEL or D or DE or FL or DL

NF followed by D or A, followed by 100 or 200, followed by coil voltage, may be followed by D or DT

NP or NA followed by D or A, followed by 100 or 200, followed by coil voltage

RMI followed by A or B, followed by 2 10 or 3 7 or 4 5, followed by coil voltage, followed by AC or DC

RMIA210110VDC, RMIA210115/120VAC ., RMIA210115VAC, RMIA21012VAC, RMIA21012VDC, RMIA210230VAC, RMIA21024VAC, RMIA21024VDC, RMIA21048VAC, RMIA21048VDC 2000-05-03, RMIA2105VDC, RMIA21060VDC, RMIA2106VAC, RMIA2106VDC, RMIA45110VDC, RMIA45110VDC/3, RMIA45115/120VAC, RMIA45115/120VAC/3, RMIA45115VAC, RMIA4512VAC, RMIA4512VDC, RMIA45230VAC, RMIA45230VAC/4, RMIA45230VAC/5, RMIA4524VAC, RMIA4524VAC/4, RMIA4524VAC/5, RMIA4524VDC, RMIA4524VDC/4, RMIA4524VDC/4/6, RMIA4548VAC, RMIA4548VDC, RMIA455VDC, RMIA4560VDC, RMIA456VAC, RMIA456VDC

RPY followed by A or B, followed by 001 or 002 or 003 or 004, may be followed by coil voltage and L or T or G or D or F or FL

Marking: Company name or tradename "ELECTROMATIC & CARLO GAVAZZI" and model designation on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2020-07-30

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."