Product Datasheet
VU24NE



VU24NE

Encl.,Volta,flush,2x12MOD,IP30,Version NCEE

Technical Features

Voltage	
Nominal voltage	400 - 400 V
Installation, mounting	
Suitable for outdoor usage	No
Mounting on	Flush mounting
Electric current	
Rated current IN	63 A
Power	
Maximum power loss per cabinet at ΔT=20K	17.50 W
Equipment	
Number of rails	2
Number of rows	2
Number of section in width	1
With lock	No
Has neutral terminal block	No
Capacity	
Number of modules	24
Number of half modules terminals per rail	48
Functions	
With conduit inlets	Yes
Dimensions	
Height	505.50 mm
Width	348 mm
Depth	94.50 mm
Built-in height	490 mm
Built-in width	314.50 mm
Cover, door	
Number of cabinet doors	1
Dimensions	
Built-in depth	89 mm
Cover, door	
Number of locks	0
Dimensions	
Number of width units	12
Cover, door	
Door/cover is transparent	No
Cabinet door type	Single door
Connectivity	
Mounting type	Screw mounting
Materials	
Material	Plastic
RAL code	9010
Colour	Pure white
Equipment	
Has earthing terminal block	Yes
Has mounting plate	No

Materials

Ultraviolet-resistant	No

Safety

Protection class	Isolation class II
Ingress Protection (IP) class	IP30
Locking type	Snap on lock Without lock
Glow wire test	650 °C
Protection class with door	IP30

Sustainability

REACh-SVHC free	Yes
RoHS conform	Yes